

Application/ Control No: 10/523,890  
Examiner: ELCENKO, ERIC J.

### IN THE CLAIMS

Please amend the claims of the present application under the provisions of 37 C.F.R. §1.121(c), as indicated below:

1. (Currently amended): Telecommunications and telephony network (AT) for controlling ~~mobile~~ (TC) ~~or fixed~~ peripheral devices at a customer premises, of the type comprising at least one local area network, at least one local residents' network (RLC), at least one regional network, at least one national network and a central network, said telecommunications and telephony network (AT) being provided for delivering signals and data between a plurality of local accesses (AL, AL1), including local users (UL), and a plurality of networks accesses (AG), through local exchanges (CL, CR), each of said local exchanges (CL, CR) including a multi-protocol gateway device (GV) for video and audio signals and data compression and conversion into IP packets bearing IP telephony data flow or data flow from the Internet and a local routing device (R) for routing said IP telephony data flow or data flow from the Internet, wherein said local users (UL) of each local access (AL, AL1) are connected to local centralizing devices (MD) through first linking means (CO) for flowing data and signals, and said local centralizing devices (MD) are in turn connected to said local exchanges (CL, CR) through second linking means (C1, C4) for flowing data and signals, while said local exchanges (CL, CR) are connected to said networks accesses (AG) through third linking means (C2, C41) for flowing data and signals, characterized in that at least said second (C1, C4) and said third linking means (C2, C41) are constituted by bidirectional satellite radio bridges (RLD, ST), wherein each bi-directional satellite radio bridge comprises a receiving/transmitting device provided at each one of the local access (AL, AL1), said network further characterized in that the first linking means (CO) are constituted by physical cables, such as telephone twisted pairs or optical fibers.

2. (Canceled)

3. (Original): Telecommunications and telephony network (AT) as claimed in claim 1, characterized in that said local routing devices (R) are connected to satellite routing

Application/ Control No: 10/523,890  
Examiner: ELCENKO, ERIC J.

devices (RS) or to radio bridges (PR), said radio bridges (PR) being able to provide connection between local residents' networks (RLC).

4. (Canceled)

5. (Original): Telecommunications and telephony network (AT) as claimed in claim 1, characterized in that each regional network is connected to the relative local residents' network (RLC) by means of a digital bidirectional satellite radio transmission or by means of communication via optical fibers.

6. (Amended): Telecommunications and telephony network (AT) for controlling ~~mobile~~ (TC) ~~or fixed~~ peripheral devices at a customer premises, of the type comprising at least one local area network, at least one local residents' network (RLC), at least one regional network, at least one national network and a central network, said telecommunications and telephony network (AT) being provided for delivering signals and data between a plurality of local accesses (AL, AL1), including local users (UL), and a plurality of networks accesses (AG), through local exchanges (CL, CR), each of said local exchanges (CL, CR) including a multi-protocol gateway device (GV) for video and audio signals and data compression and conversion into IP packets bearing IP telephony data flow or data flow from the Internet and a local routing device (R) for routing said IP telephony data flow or data flow from the Internet, wherein said local users (UL) of each local access (AL, AL1) are connected to local centralizing devices (MD) through first linking means (CO) for flowing data and signals, and said local centralizing devices (MD) are in turn connected to said local exchanges (CL, CR) through second linking means (C1, C4) for flowing data and signals, while said local exchanges (CL, CR) are connected to said networks accesses (AG) through third linking means (C2, C41) for flowing data and signals, characterized in that at least said second (C1, C4) and said third linking means (C2, C41) are constituted by bidirectional satellite radio bridges (RLD, ST), wherein each bi-directional satellite radio bridge comprises a receiving/transmitting device provided at each one of the local access (AL, AL1), said network further characterized in that the first linking means (CO) are constituted by physical cables.

Application/ Control No: 10/523,890  
Examiner: ELCENKO, ERIC J.

7. (Amended): Telecommunications and telephony network (AT) for controlling ~~mobile~~ (TC) ~~or fixed~~ peripheral devices at a customer premises, of the type comprising at least one local area network, at least one local residents' network (RLC), at least one regional network, at least one national network and a central network, said telecommunications and telephony network (AT) being provided for delivering signals and data between a plurality of local accesses (AL, AL1), including local users (UL), and a plurality of networks accesses (AG), through local exchanges (CL, CR), each of said local exchanges (CL, CR) including a multi-protocol gateway device (GV) for video and audio signals and data compression and conversion into IP packets bearing IP telephony data flow or data flow from the Internet and a local routing device (R) for routing said IP telephony data flow or data flow from the Internet, wherein said local users (UL) of each local access (AL, AL1) are connected to local centralizing devices (MD) through first linking means (CO) for flowing data and signals, and said local centralizing devices (MD) are in turn connected to said local exchanges (CL, CR) through second linking means (C1, C4) for flowing data and signals, while said local exchanges (CL, CR) are connected to said networks accesses (AG) through third linking means (C2, C41) for flowing data and signals, characterized in that at least said second (C1, C4) and said third linking means (C2, C41) are constituted by bidirectional satellite radio bridges (RLD, ST), said bidirectional satellite radio bridges are further characterized in that they are low power consumption units, each low-power bidirectional satellite bridge being supplied power by means of a solar power system, wherein each bi-directional satellite radio bridge comprises a receiving/transmitting device provided at each one of the local access (AL, AL1), said network further characterized in that the first linking means (CO) are constituted by physical cables.

8. (New): A telecommunications and telephony network (AT) as defined in claim 6 where the physical cables are selected from telephone twisted pairs and optical fibers.

9. (New): A telecommunications and telephony network (AT) as defined in claim 7 where the physical cables are selected from telephone twisted pairs and optical fibers.